

COVERT CAMERA SMOKE DETECTOR



**High Resolution Color Camera
Low Light Capable too --- 0.01 LUX!!**

Our BEST Covert Camera EVER!

This Covert Smoke Detector camera uses Sony Camera along with a 600TV Line Board.

600 Lines of Resolution - OSD Menu - 3.7mm Pinhole Wide-Angle Lens - and a wide temperature range of 14° to 122°F - makes this a high performing camera for covert surveillance.

12V DC

Model #: RGC-WSD	
Type	Color CCD Camera
Pick Up Device	1/3" Sony CCD Image Sensor
Picture Elements	EIA/NTSC: 510 H x 492 V CCIR/PAL: 500 H x 582 V
Horizontal Resolution	600 TVL
Minimum Illumination	0.01 Lux
Horizontal Sync. Frequency	EIA/NTSC:15.734 KHZ CCIR/PAL: 15.625 KHZ
Vertical Frequency	EIA/NTSC: 60 HZ CCIR/PAL: 50 HZ
Clock Frequency	EIA/NTSC: 19.0699 MHZ CCIR/PAL: 18.9375 MHZ
Function	OSD Menu (mirror function)
Lens	3.7mm Pinhole Lens
Video Output	1Vp-p, 75 ohms
Gamma	0.45
Power Supply	DC12 V
Power Consumption	400 mA
Storage Temperature	-22°F ~ 140°F
Operation Temperature	14°F ~ 113°F



201 N Elm St. • Kemp, Texas 75143
Toll Free: 866-301-CCTV • Phone: 903-498-3240 • Fax: 903-498-8989
www.rugged-cctv.com